


## 'FTG' COMB BUSBAR (GERMANY)



- Impulse Voltage Strength :  $\geq 4.5\text{kV}$   
 Max. Operating Voltage : 1 Phase : 1000V AC / DC , 2 / 3 / 4 Phase : 690 V AC / DC  
 Short Circuit Rating : ICC 25kA  
 Protection Class : IP 20  
 Dielectric Strength : PC - ABS , PVC  $> 32\text{kV} / \text{mm}$   
 Insulation : PC-ABS , PVC Lead Free (Flame Resistant)  
 Feeding Ratings : 130A at Center Feed , 80A at Side Feed

Item	Part No.	Description	No. of Module	Length (mm)
1	CBB 1F-G	1 Phase Comb Busbar, Fork	57	1000
2	CBB 1P-G	1 Phase Comb Busbar, Pin	57	1000
3	CBB 2F-G	2 Phase Comb Busbar, Fork	56	1000
4	CBB 2P-G	2 Phase Comb Busbar, Pin	56	1000
5	CBB 3F-G	3 Phase Comb Busbar, Fork	57	1014
6	CBB 3P-G	3 Phase Comb Busbar, Pin	57	1012
7	CBB 4F-G	4 Phase Comb Busbar, Fork	56	1000
8	CBB 4P-G	4 Phase Comb Busbar, Pin	56	1000

## 'FTG' FEEDING TERMINALS (GERMANY)



- Maximun Voltage : 690Vac / 1000Vdc  
 Maximun Amphere : 125A  
 Protection Class : IP20

Item	Part No.	Description	Single/Multi Wire mm <sup>2</sup>	Wire With Sleeve mm <sup>2</sup>
1	FTP-35/50-T	'FTG' Feeding Terminals , 35/50mm <sup>2</sup> , Pin Top Entry	6 - 50	4 - 35
2	FTP-35/50-L	'FTG' Feeding Terminals , 35/50mm <sup>2</sup> , Pin Left Entry	6 - 50	4 - 35
3	FTP-35/50-R	'FTG' Feeding Terminals , 35/50mm <sup>2</sup> , Pin Right Entry	6 - 50	4 - 35