


Engine Powered Aerial Work Platforms
SPECIFICATIONS




Main Features

- Oscillating Axle
- Control ADE® System
- 110V-AC Receptacle in Platform
- Operator Tool Tray

	600S	600SJ	660SJ	600SC	660SJC
600 Series Telescopic Boom Lifts					
Platform Height	60 ft 3 in. (18.36 m)	60 ft 5 in. (18.44 m)	66 ft 8 in. (20.32 m)	60 ft 3 in. (18.36 m)	66 ft 8 in. (20.32 m)
Platform Capacity—Restricted	1,000 lb (454 kg)	500 lb (227 kg)	N/A	1,000 lb (454 kg)	500 lb (227 kg)
Platform Capacity—Unrestricted	500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)
Horizontal Outreach	49 ft 6 in. (15.09 m)	50 ft 5 in. (15.36 m)	56 ft 9 in. (17.3 m)	49 ft 6 in. (15.09 m)	56 ft 9 in. (17.30 m)
Overall Width	7 ft 11 in. (2.42 m)	7 ft 11 in. (2.42 m)	7 ft 11 in. (2.41 m)	8 ft 2 in. (2.49 m)	8 ft 2 in. (2.49 m)
Weight	22,750 lb (10,319 kg)	23,900 lb (10,841 kg)	27,600 lb (12,519 kg)	22,500 lb (10,206 kg)	27,100 lb (12,293 kg)
Dual Fuel Engine—GM Vortec 3000 MPFI	82 hp (61.1 kW)	82 hp (61.1 kW)	82 hp (61.1 kW)	—	—
Diesel Engine—Deutz D2011L04 w/EGR Caterpillar 3044C	49 hp (36.5 kW) 63.3 hp (47.2 kW)	49 hp (36.5 kW) 63.3 hp (47.2 kW)	49 hp (36.5 kW) 63.3 hp (47.2 kW)	64 hp (47 kW) 63.3 hp (47.2 kW)	64 hp (47 kW) 63.3 hp (47.2 kW)
Available Options					
Soft Touch System 6 ft/8 ft	•	•	•	◦	◦
2500W Generator	•	•	•	•	•
36 x 72 in. (0.91 x 1.83 m) Platform	•	•	•	•	•
43.5 lb (19.73 kg) Propane Tank	•	•	•	◦	◦
Arctic Package—Deutz and CAT	•	•	•	•	•
Cold Weather Start Kit—Includes engine block heater, battery heater and oil tank heater.	•	•	•	•	•
Flashing Amber Beacon	•	•	•	•	•
Hostile Environment Kit—Includes boom wipers, cylinder bellows and console cover.	•	•	•	•	•

Engine Powered Aerial Work Platforms
SPECIFICATIONS



Main Features

- Narrow Fixed Width—Low GVW
- Control ADE® System
- 110V-AC Receptacle in Platform
- Operator Tool Tray

	800S	860SJ
800 Series Telescopic Boom Lifts		
Platform Height	80 ft (24.38 m)	86 ft (26.21 m)
Platform Capacity—Restricted	1,000 lb (454 kg)	750 lb (340 kg)
Platform Capacity—Unrestricted	500 lb (227 kg)	500 lb (227 kg)
Horizontal Outreach	71 ft (21.64 m)	75 ft (22.9 m)
Overall Width	8 ft 2 in. (2.49 m)	8 ft 2 in. (2.49 m)
Weight	33,200 lb (15,059 kg)	36,400 lb (16,510 kg)
Dual Fuel Engine—GM Vortec 3000 MPFI	82 hp (61.1 kW)	82 hp (61.1 kW)
Diesel Engine—Deutz D2011L04 w/EGR Caterpillar 3044C	64 hp (47 kW) 63.3 hp (47.2 kW)	64 hp (47 kW) 63.3 hp (47.2 kW)
Available Options		
Light Package—Includes head and tail lights and platform worklights.	•	•
Tow Package	•	•
36 x 72 in. (0.91 x 1.83 m) Platform	•	•
36 x 96 in. (0.91 x 2.44 m) Fall Arrest Platform—Rear Entry	•	•
Cold Weather Start Kit—Includes engine block heater, battery heater and oil tank heater.	•	•
Arctic Package	•	•