


Engine Powered Aerial Work Platforms SPECIFICATIONS




Main Features

- Oscillating Axle on 3394RT and 4394RT
- 4-Wheel Drive
- Automatic Transmission
- 4 ft (1.22 m) Manual Deck Extension
- 110V-AC Receptacle in Platform

| | 260MRT | 3394RT | 4394RT |
|--|------------------------------|------------------------------|------------------------------|
| Rough Terrain Scissor Lifts | | | |
| Platform Height | 26 ft (7.92 m) | 33 ft (10.06 m) | 43 ft (13.11 m) |
| Platform Capacity | 1,250 lb (567 kg) | 2,250 lb (1,020 kg) | 1,500 lb (680 kg) |
| Capacity on Extension | 300 lb (136 kg) | 500 lb (227 kg) | 500 lb (227 kg) |
| Capacity w/Dual Extensions | N/A | 2,000 lb (907 kg) | 1,250 lb (567 kg) |
| Platform Size | 65 x 102 in. (1.65 x 2.59 m) | 86 x 150 in. (2.18 x 3.18 m) | 86 x 150 in. (2.18 x 3.81 m) |
| Overall Width | 5 ft 9 in. (1.75 m) | 7 ft 10 in. (2.39 m) | 7 ft 10 in. (2.39 m) |
| Weight | 7,360 lb (3,338 kg) | 11,910 lb (5,402 kg) | 15,300 lb (6,940 kg) |
| Dual Fuel Engine—Kubota GM Vortec 3000 MPFI | 24.5 hp (18.3 kW) | — | — |
| | — | 82 hp (61.1 kW) | 82 hp (61.1 kW) |
| Diesel Engine—Kubota Deutz D2011L03 | 26 hp (19.4 kW) | — | — |
| | — | 49 hp (36.5 kW) | 49 hp (36.5 kW) |
| Available Options | | | |
| 3000 Watt, 110V-AC Power Pack Generator | • | ◦ | ◦ |
| 3500 Watt, 110V-AC Generator | ◦ | • | • |
| 33.5 lb (15.19 kg) Propane Tank | • | ◦ | ◦ |
| 43.5 lb (19.73 kg) Propane Tank | ◦ | • | • |
| Flashing Amber Beacon | • | • | • |
| Leveling Jacks | • | • | • |
| Platform Worklights | • | • | • |
| Self-Closing Entry Gate | • | • | • |
| 1/2 in. Air Line to Platform | • | • | • |
| Dual 48 in. Manual or Powered Deck Extensions | ◦ | • | • |
| Cold Weather Start Kit (Deutz)—Includes battery heater and hydraulic tank heater. Glow plugs standard on Deutz engine. | ◦ | • | • |
| Cold Weather Start Kit (GM)—Includes battery heater, hydraulic tank heater and block heater. | ◦ | • | • |

For complete specifications, visit www.jlg.com

Engine Powered Aerial Work Platforms SPECIFICATIONS




Main Features

- Oscillating Axle
- 2-Wheel Drive or 4-Wheel Drive
- Control ADE® System
- 110V-AC Receptacle in Platform
- Operator Tool Tray
- Easy Access Swing-out Engine Tray

| | 450A | 450AJ |
|---|------------------------------------|------------------------------------|
| 450 Series II Articulating Boom Lifts | | |
| Platform Height | 45 ft (13.72 m) | 45 ft (13.72 m) |
| Platform Capacity—Unrestricted | 500 lb (227 kg) | 500 lb (227 kg) |
| Horizontal Outreach | 24 ft 6 in. (7.47 m) | 24 ft 6 in. (7.47 m) |
| Up and Over Height | 25 ft 2 in. (7.67 m) | 25 ft 2 in. (7.67 m) |
| Overall Width | 6 ft 10 in. (2.08 m) | 6 ft 10 in. (2.08 m) |
| Weight | 15,100 lb (6,849 kg) | 16,000 lb (7,257 kg) |
| Dual Fuel Engine—GM Vortec 3000 MPFI | 82 hp (61 kW) | 82 hp (61 kW) |
| Diesel Engine—Perkins 404C-22 Caterpillar C2.2 | 49 hp (36.5 kW) 49 hp (36.5 kW) | 49 hp (36.5 kW) 49 hp (36.5 kW) |
| Available Options | | |
| Semi-Track | • | • |
| 1/2 in. Air Line to Platform | • | • |
| SkyPower® | • | • |
| Fall Arrest Platform | • | • |
| Cold Weather Start Kit—Includes battery blanket, hydraulic tank heater, and block heater. | • | • |
| Arctic Package | • | • |

| | 600A | 600A Narrow | 600AJ | 600AJ Narrow |
|---|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| 600 Series Articulating Boom Lifts | | | | |
| Platform Height | 60 ft 5 in. (18.42 m) | 60 ft 5 in. (18.42 m) | 60 ft 7 in. (18.46 m) | 60 ft 7 in. (18.46 m) |
| Platform Capacity—Restricted | 1,000 lb (454 kg) | 1,000 lb (454 kg) | 500 lb (227 kg) | 500 lb (227 kg) |
| Platform Capacity—Unrestricted | 500 lb (227 kg) | 500 lb (227 kg) | 500 lb (227 kg) | 500 lb (227 kg) |
| Horizontal Outreach | 39 ft 7 in. (12.07 m) | 39 ft 7 in. (12.07 m) | 39 ft 9 in. (11.81 m) | 39 ft 9 in. (11.81 m) |
| Up and Over Height | 26 ft 7 in. (8.1 m) | 26 ft 7 in. (8.1 m) | 26 ft 7 in. (8.1 m) | 26 ft 7 in. (8.1 m) |
| Overall Width | 8 ft (2.44 m) | 7 ft (2.13 m) | 8 ft (2.44 m) | 7 ft (2.13 m) |
| Weight | 22,150 lb (10,047 kg) | 24,100 lb (10,931 kg) | 23,050 lb (10,455 kg) | 24,200 lb (10,977 kg) |
| Dual Fuel Engine—GM Vortec 3000 MPFI | 82 hp (61 kW) | 82 hp (61 kW) | 82 hp (61 kW) | 82 hp (61 kW) |
| Diesel Engine—Deutz D2011L04 Caterpillar 3044C | 49 hp (36.5 kW) 63.3 hp (47.2 kW) | 49 hp (36.5 kW) 63.3 hp (47.2 kW) | 49 hp (36.5 kW) 63.3 hp (47.2 kW) | 49 hp (36.5 kW) 63.3 hp (47.2 kW) |
| Available Options | | | | |
| 1/2 in. Air Line to Platform | • | • | • | • |
| SkyPower® | • | • | • | • |
| Fall Arrest Platform | • | ◦ | • | ◦ |
| 43.5 lb (19.73 kg) Propane Tank | • | • | • | • |
| Cold Weather Start Kit—Includes engine block heater, battery heater, and oil tank heater. | • | • | • | • |
| Arctic Package | • | • | • | • |



Main Features

- Choice of Chassis Width
- 2-Wheel Drive or 4-Wheel Drive
- Oscillating Axle
- Control ADE® System
- 110V-AC Receptacle in Platform
- Operator Tool Tray
- Easy Access Swing-out Engine Tray